

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 3, 5, and 13 and ADD new claim 24, in accordance with the following:

1. (CURRENTLY AMENDED) An apparatus for controlling the power of a monitor, comprising:

a computer selectively outputting a predetermined signal when the computer is powered on and off;

a monitor comprising a memory separate from a power control unit to control power supply within the monitor, the power control unit to-receivinge the predetermined signal and selectively performing control powering on and off of the monitor according to the predetermined signal; and

a video card processing and transmitting a video signal to the monitor;

wherein the predetermined signal output from the computer is output from a predetermined pin of the video card,

wherein the predetermined signal is transmitted to the monitor independent of whether the monitor is powered on and independent of whether the monitor is powered off, and

wherein, when the monitor is powered off, ~~a-the memory of the monitor~~ is powered by the predetermined signal to provide the computer access to monitor information stored in the memory.

2. (CANCELED)

3. (CURRENTLY AMENDED) An apparatus for controlling the power of a monitor, comprising:

a computer selectively outputting a predetermined signal when the computer is powered on and off;

a monitor to receive the predetermined signal and selectively performing powering on and off of the monitor according to the predetermined signal; and

a video card processing and transmitting a video signal to the monitor;
wherein the predetermined signal output from the computer is output from a predetermined pin of the video card; and
wherein the predetermined signal is transmitted to the monitor independent of whether the monitor is powered on and independent of whether the monitor is powered off, so that monitor information in the monitor is accessible by the computer based upon the transmission of the predetermined signal, wherein the monitor comprises:

a memory storing the monitor information, wherein the monitor information is accessible by the computer, independent of whether the monitor is powered on and independent of whether the monitor is powered off, based upon the transmission of the predetermined signal;

a power control unit to control power supply within the monitor, the power control unit
comparing a reference level with a level of the predetermined signal, detecting a state of power of the computer based on a result of the comparison, and outputting a monitor power control signal; and

a power supply unit to selectively perform selective supplying and cutting off of power to the monitor ~~in accordance with~~based on the monitor power control signal output from the control unit,

wherein the memory is separate from the power control unit.

4. (PREVIOUSLY PRESENTED) The apparatus of claim 3, wherein the predetermined signal drives the memory so that the monitor information stored in the memory is accessible by the computer.

5. (CURRENTLY AMENDED) The apparatus of claim 3, wherein the power control unit outputs a first control signal to supply power to the monitor in response to the level of the predetermined signal being higher than the reference level, and the power control unit outputs a second control signal to cut off power to the monitor in response to the level of the predetermined signal being lower than the reference level.

6. (PREVIOUSLY PRESENTED) The apparatus of claim 5, wherein the level of the predetermined signal is 5V in response to the computer being powered on, and 0V in response to the computer being powered off.

7. (PREVIOUSLY PRESENTED) The apparatus of claim 1, further comprising a serial cable, wherein the predetermined signal is transmitted from the computer to the monitor via the serial cable.

8-12. (CANCELED)

13. (CURRENTLY AMENDED) A method of controlling the power of a monitor, the method comprising:

receiving, by a power control unit controlling power supply within the monitor, -a predetermined signal from a computer based upon the computer being powered; and

selectively powering, by the power control unit, the monitor on and off according to the predetermined signal,

wherein the predetermined signal is transmitted to the monitor independent of whether the monitor is powered on and independent of whether the monitor is powered off, and

wherein the receiving of the predetermined signal includes the power control unit supplying power from the predetermined signal to a memory in the monitor, separate from the power control unit, storing monitor information, so that the monitor information in the memory is accessible by the computer based upon the predetermined signal when the monitor is powered off.

14. (CANCELED)

15. (PREVIOUSLY PRESENTED) The method of claim 13, wherein the powering on and off of the monitor further comprises:

detecting a level of the received predetermined signal;

supplying power to the monitor in response to the level of the predetermined signal being higher than a reference level; and

cutting off power to the monitor in response to the level of the predetermined signal being lower than the reference level.

16.-23. (CANCELED)

24. (NEW) An apparatus for controlling the power of a monitor comprising:

 a memory storing a monitor information, the monitor information being accessible by a computer, independent of whether the monitor is powered on and independent of whether the monitor is powered off, based on a transmission of a predetermined signal;

 a power control unit to control power supply within the monitor, the power control unit comparing a reference level with a level of the predetermined signal, detecting a state of power of the computer based on a result of the comparison, and outputting a monitor power control signal; and

 a power supply unit to perform selective supplying and cutting off of power to the monitor based on the monitor power control signal output from the power control unit,

 wherein the memory is separate from the power control unit, and

 wherein the predetermined signal is output when the computer is powered on and off and the monitor selectively performs powering on and off according to the predetermined signal.